



SUPERSEAL Carpet Subfloor Product Specification Sheet

Phone: 1-800-571-1877
Fax: 604-576-2458

www.superseal.ca
info@superseal.ca

September 01, 2010 - present

When carpet gets wet, any trapped moisture can damage your flooring attracting mold and mildew and creating expensive repairs. Carpet Subfloor Membrane provides full surface ventilation and maximum protection for your new floor.

Part #	Roll Sizes
DD10886	3'3" x 32.8' - 108 ft ² - (1.0 x 10m)
DD10162	3'3" x 50' - 162 ft ² - (1.0 x 15m)

Properties	Values
Material - Dimpled Sheet	High-Density Polyethylene (HDPE)
Color - Dimpled Sheet	Black
Thickness - Dimpled Sheet	0.5 mm (20mil)
Area Weight (approx)	500 g/m ²
Dimple Height	2.8mm (1/8")
Compressive Strength	750 kN/m ² (15,600 psf)
Service Temperature Range	-40° C to +80° C

SUPERSEAL Carpet Subfloor is made from up to 80% recycled plastic and is;

- **IMPERVIOUS to** root penetration and rot proof.
- **RESISTANT to;** fungus and bacterial attack, concentrated acetic acid, alcoholic beverages, ammonia aqueous, diesel fuel, dishwashing soap, fruit juices, hydrofluoric acid up to 20%, Hydrofluoric acid up to 35%, laundry detergents, methanol, milk, motor oil, concentrated potassium hydroxide, silicone oil, soap solution - aqueous, concentrated sodium hydroxide, sulfuric acid up to 40%, vegetable oils & fats, cold water, hot water, saltwater.
- **CONDITIONALLY RESISTANT to;** acetone, benzene, ozone, gasoline (petrol) and toluene.

Areas of Application / Benefits

- For use wherever carpet or laminate is installed to control moisture and to increase floor temperature
- Residential and commercial applications such as basements and wood substrates
90% lighter and 10x faster than plywood
- Makes floors more comfortable to walk on
- Compatible with heated floor systems
- No need for plywood or nails when installing carpet or laminate
Warmer and softer floors

SUPERSEAL warranties this product for a period of 20 years and is resistant to a wide range of chemicals, resistant to fungus and bacterial attack, impervious to root penetration and rot proof. In the event this product fails to meet these requirements, the said amount of material shall be supplied free of charge. There are no warranties beyond this expressed as stated above. **SUPERSEAL** assumes no responsibility for any other losses or damages, labour, materials, punitive, incidental or consequential or otherwise. Proof of purchase must be provided at time of claim.