SUPERSEAL Construction Products Ltd.

SUPERSEAL WATERPROOFING

MATERIAL SAFETY DATA SHEET

Preparation date January 1st, 2024

Supplier: SUPERSEAL Construction Products Ltd. PO Box 61646 Brookswood RPO Langley B.C. V3A-8C8 Canada

Phone: 1-800-571-1877 Fax: 1-778-277-1255

Plants: 19370 Enterprise Way Surrey B.C. V3S-6J9 Canada

THIS PRODUCT IS NOT SUBJECT TO THE CONTROLS OF PRODUCTS OR THE TRANSPORTATION DANGEROUS GOODS REGULATIONS.

SECTION I MATERIAL IDENTIFICATION

TRADE NAME:	SUPERSEAL Waterproofing
MATERIAL USE:	Foundation waterproofing and dampproofing
T.D.G. CLASSIFICATION:	NON REGULATED

WHMIS CLASSIFICATION: NON REGULATED

EMERGENCY TELEPHONE #:

SUPERSEAL Construction Products Ltd.1-800-571-187724-HOUR EMERGENCY AND SDS HELP:Canutec: 1-613-966-6666

SECTION II HAZRDUS INGREDIENTS

COMPONENT	CAS#	% (BY MASS)	LC50 (ppm) (rat inhal)	LB50 (mg/kg) (rat oral)
Complex mixture of bitumens	n/a	40-70	n/a	n/a
Surfactants	n/a	0.5-2.0	n/a	n/a
Water	7732 -18-5	30-60	n/a	n/a
Polymer dispersion		5-25	n/a	n/a

SECTION III PHYSICAL PROPERTIES

Odour and appearance: Odour threshold: Specific gravity: Brown liquid, slight resinous odour n/a 1.00 (approx.) Page **1** of **3**



SUPERSEAL Construction Products Ltd.

SUPERSEAL WATERPROOFING

Coefficient of water/oil distribution:	n/a
Vapour pressure (mm Hg):	17 @20ºC (water)
Boiling Point:	100ºC
Freezing point:	0ºC
pH:	7-9
Vapour density (air = 1):	>1
Evaporation rate (nBuAcetate = 1):	<1
Volatiles %:	40-60 (water)
Solubility in water:	partially soluble

SECTION IV FIRE AND EXPLOSION DATA

Means of extinction:	n/a
Sensitivity to mechanical impact/static discharge:	n/a
Flash point (method):	n/a (non-combustible)
Upper flammable limits %:	n/a
Lower flammable limits:	n/a
Autoignition temperature:	n/a
Special firefighting instructions:	n/a
Unusual fire and explosion hazards:	Product will not burn but may splatter if temperature exceeds the boiling point.

SECTION V FIRE REACTIVITY DATA

Chemical stability: Incompatible materials: Hazardous decomposition products:	Stable Will react with alkaline sensitive materials such as acids and certain metals. Contact with reactive metals such as aluminum or magnesium will result in the formation of explosive hydrogen gas. Avoid heating above 200°C. At elevated temperatures hazardous vapours can be released, including carbon monoxide, hydrogen chloride, organic acids and aldehydes.
Hazardous polymerization: Exposure limit: Inhalation:	Will not occur. SECTION VI HEALTH INFORMATION n/a n/a

Inhalation: Skin: Eyes: Ingestion: Chronic effects: n/a n/a Adhesion Adhesion, irritation. Blockage of digestive and/or respiratory tract. n/a

Page 2 of 3

SUPERSEAL Construction Products Ltd.

SUPERSEAL WATERPROOFING

EMERGENCY AND FIRST AID PROCEDURES

Inhalation: Skin:	n/a This is an alkaline product. If splashed on the skin immediately wash thoroughly with fresh water. If the product has dried on the skin massage the area with medical grade mineral oil, baby oil, or edible oil then wash with soap and water. If irritation persists seek medical attention.
Eyes:	Flush thoroughly with fresh water for at least 10 minutes. Seek medical attention.
Ingestion:	DO NOT INDUCE VOMITING. Seek medical attention.

SECTION VII SPILL PROCEDURES

In the event of a spill: Dike and contain. Spread oil dry / kitty litter or sand to absorb. Use a flat shovel and a broom to pick up for disposal. Transfer to containers for recovery or disposal. Keep out of sewers

Waste disposal method: Follow federal, provincial and local regulations regarding disposal.

SECTION VIII SPECIAL PROTECTION

Respiratory protection:	n/a
Ventilation:	n/a
Protective gloves:	Recommended
Eye protections:	Safety glasses/splash goggles recommended
Other protective equipment:	long sleeves, loose clothing recommended

SECTION IX SPECIAL PRECAUTIONS

Storage and handling: Special shipping instructions: Keep containers tightly closed when not I use. KEEP FROM FREEZING Not regulated by the Transportation of Dangerous Goods Regulations

Prepared by: Preparation date: **SUPERSEAL** Construction Products Ltd. September 01, 2023

The information contained herein on available data and is provided for information only. **SUPERSEAL** Construction Products Ltd. makes no warranties, guarantees or conditions, expressed or implied, regarding the accuracy of the data or it's use therein. **SUPERSEAL** Construction Products Ltd. will not be liable for any damages arising from the use of the information or described on this sheet.

Page 3 of 3

